

# BOND ALL EXTERIOR



**BOND ALL EXTERIOR** is an exterior grade, water based, surface bonding agent applied prior to placing new plaster and Portland cement based mixes over masonry, concrete, brick, block, stone, plaster, drywall, wonderboard, precast concrete, wood, tile and EPS board.

- Bonds new plaster, mortar, concrete and stucco to a variety of surfaces
- Heavy bodied, won't sag
- Re-emulsifiable
- Wet plaster, concrete, mortar and stucco mixes may be applied over Bond All Exterior up to seven days after it has been applied
- Non-flammable
- VOC compliant
- May be applied over "green" concrete
- Meets ASTM C-1059

Bonding Agent	May be applied by brush, roller or spray
Packaging	Quart bottle (12/case) 1G bottle (4/case, 108/pallet) 5G pail (36/pallet), 55G drum
Coverage per gallon	Block/Brick = 150-250 ft <sup>2</sup> Concrete = 250-350 ft <sup>2</sup> Plaster = 300-400 ft <sup>2</sup>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing	Stir well before using
Set Time	Apply wet mixes when Bond All Exterior becomes tacky or dry up to seven days after application
Color	Milky white but dries clear



Phone: 800-442-5535  
Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)