

SILOXANE WB



SILOXANE WB is a clear, water based, deep penetrating water repellent designed to be applied over untreated concrete pavers, brick, block, concrete, stucco, flagstone, granite, natural stone, limestone and bluestone. Breathable, protects without forming a film or leaving a sheen.

- Breathable, does not form a film or leave a sheen
- Dries clear on most substrates maintaining the natural appearance
- Easily applied by brush, roller or low pressure pump sprayer
- Protects against repeated freeze thaw cycles
- UV light resistant
- Reduces efflorescence
- VOC compliant
- One coat coverage for most applications
- Exterior or interior use

Water Repellent	May be applied by brush, roller or low pressure pump sprayer
Packaging	1G can (4/case,108/pallet) 5G pail (36/pallet), 55G drum
Coverage per gallon	Concrete = 120-220 ft ² Block/Brick = 80-150 ft ² Split Rib Block = 50-100 ft ²
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing	Stir well. Not to be thinned.
Dry Time	12-24 hours at 70°F, 50% RH
Recoat Time	If second coat is required, must be applied wet-on-wet



Phone: 800-442-5535
Fax: 978-453-2416
www.umaco.com