

# SELF-LEVELER 4000



**SELF-LEVELER 4000** is a single-component, self-leveling, floor resurfacer and underlayment which can be poured or pumped over concrete, terrazzo, ceramic tile, and wood flooring from a feather-edge up to 2" in a single pour. Areas to be resurfaced must be primed with Bond All Exterior.

- Completely self leveling
- Interior or exterior use
- Just add water
- Polymer modified
- May be poured or pumped
- Can be applied up to 2" in a single pour
- High compressive and flexural strengths
- Water resistant
- Provides dramatic savings in time and labor over conventional underlayments
- An excellent underlayment for tile, vinyl, carpet, etc.

Resurfacing Mortar	Pour or pump from feather-edge up to 2"
Packaging	50 lb bag (49 /pallet)
Coverage per 50 lb bag	1/8" = 55 ft <sup>2</sup> 1/4" = 27 ft <sup>2</sup>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing per 50 lb bag	5 to 5-1/2 quarts of water
Working Time	15 minutes at 70°F
Set Time	4-8 hours at 70°F
Color	Gray



Phone: 800-442-5535  
 Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)