

SCREEN GRADE CALCIUM CARBONATE

XO WHITE™



XO WHITE™ is a dry ground marble with a coarse particle size that is controlled between 16 and 40 mesh screens. In addition to textured coatings and acid neutralization, XO WHITE is NSF registered for use in water filtration systems.

DAT001CK
August 2004
©IMERYS 2000
Second Edition

All product names are
trademarks of IMERYS.

TYPICAL VALUES

Source:	(M) Marble Hill, GA
% CaCO ₃	95
% Acid Insolubles	2
% SiO ₂	0.3
% Moisture	0.15
% Plus 16 mesh	1
% Minus 40 mesh	10
Hardness (Mohs)	3
Index of refraction	1.6
Specific Gravity	2.7
Solid Density (lb/gal)	22.7
Bulk Density (lb/ft ³)	
Loose	90
Packed	105

IMERYS
100 Mansell Court East
Suite 300
Roswell, GA 30076

General:
Tel: (770) 594.0660
Fax: (770) 645.3384

Customer Service:
Tel: (888) 277.9636
Fax: (770) 645.3631

IMERYS is a business name
of IMERYS Pigments, Inc.,
IMERYS Kaolin, Inc. and
IMERYS Marble, Inc.
Registered in the USA.

APPLICATIONS

XO WHITE is suited for use in the following applications:

- Textured Coatings & Stuccos for Interior & Exterior Use
- Water Filtration System (NSF listed)
- Acid Neutralization

This information is believed to be correct. However, this information does not constitute any representation, condition or warranty, nor do we guarantee results to be obtained. All recommendations and sales are made on the condition that we will not be held liable for any damages resulting from their use. This provision may not be changed by any of our representatives.

