

CONCRETE CURE & SEAL



CONCRETE CURE & SEAL is a waterborne acrylic emulsion designed to cure, seal, harden and dustproof new or older concrete substrates. Forms a membrane on new concrete which retains water, allowing normal hydration. Contains no fillers, extenders, waxes or flammable solvents.

- Cures, seals, hardens & dust proofs concrete
- Clear, gloss finish
- Helps to eliminate scaling
- Excellent for anti-spalling
- Does not blush or yellow
- UV resistant
- Helps to prevent against efflorescence
- Protects against many oils, acids, salt, alkalis, fungus, grease, spalling and damage from sudden rainfalls
- Protects aluminum, copper and steel from concrete stains

Concrete Cure & Seal	May be applied by brush, roller or airless sprayer
Packaging	1G can (4/case,108/pallet) 5G pail (36/pallet), 55G drum
Coverage per gallon	<u>Steel Troweled Concrete</u> 200-250 ft ² <u>Broom Finished Concrete</u> 100-150 ft ²
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing	Stir well. Not to be thinned.
Dry To Touch	30 minutes at 80°F, 50% RH
Normal Traffic	12 hours at 80°F, 50% RH



Phone: 800-442-5535
Fax: 978-453-2416
www.umaco.com