

# FLASH-PATCH



**FLASH-PATCH** is a fast setting (20 minutes), cement based, single component, patching, topping and underlayment material applied over concrete, masonry & plywood surfaces from feather-edge up to 1/2". Its fast set time allows for quick finishing and shortened down time.

- Fast setting (20 minutes).
- Easy to use, just add water
- Polymer modified
- Non shrink
- For applications that requires a maximum build up of 1/2"
- Trowels easily
- May be feather-edged
- Superior adhesion and flexural strengths
- High compressive strength
- A superior underlayment for tile, carpet, etc.
- Resurfaces floors, ramps, sidewalks, steps, etc.

Resurfacing Mortar	Apply by trowel from feather-edge up to 1/4"
Packaging	50 lb bag (49/pallet) 8 lb pail (6/case)
Coverage per 50 lb bag	1/8" = 50 ft <sup>2</sup> 1/4" = 25 ft <sup>2</sup>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing per 50 lb bag	3-1/2 quarts water
Working Time	15 minutes at 70°F
Set Time	20 minutes at 70°F
Color	Gray



Phone: 800-442-5535  
 Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)