

# FEATHER-EDGE



**FEATHER-EDGE** is a fast setting, cement based, polymer modified, patching and leveling material which provides a smooth, true feather-edge finish prior to the installation of floor coverings such as ceramic tile, VCT, sheet vinyl and carpeting. Interior use only.

- Provides a smooth finish prior to installing a variety of floor coverings
- May be applied from a true featheredge up to 1/2"
- Fast controlled initial set (10 minutes)
- Mixes easily with just water
- Polymer modified
- Can be applied over concrete, wood, terrazzo, ceramic and quarry tile
- Exceptional bond strength
- Mold and mildew resistant
- For interior use only

Resurfacing Mortar	Apply by trowel from feather-edge up to 1/2"
Packaging	25 lb bag (100/pallet) 10 lb bag (4/case)
Coverage per 10 lb bag	1/8" = 33 ft <sup>2</sup> 1/4" = 17 ft <sup>2</sup>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing per 10 lb bag	1-1/2 quarts water
Working Time	10 minutes at 70°F
Set Time	20 minutes at 70°F
Color	Gray



Phone: 800-442-5535  
 Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)