

TRANSEAL



TRANSEAL is a clear, solvent based, high gloss, acrylic sealer designed to be applied over properly prepared concrete pavers, brick, block, concrete, stucco, natural stone, flagstone, granite, limestone and bluestone. Forms a durable, flexible film providing long lasting protection.

- Available in Clear Gloss and Clear Matte finish
- Forms a durable film
- Impervious to water, salts, grease, petroleum oils, aliphatic solvents and other common chemicals
- Highlights the natural beauty & color of natural stone, flagstone, granite, bluestone, etc.
- Protects against repeated freeze thaw cycles
- Reduces efflorescence
- Quick drying
- Exterior use only

| | |
|-------------------------|--|
| Masonry Sealer | May be applied by brush or roller |
| Packaging | Quart can (12/case) 1G can (4/case, 108/pallet) 5G pail (36/pallet), 55G drum |
| Coverage per gallon | Slate/Flagstone = 250-300 ft ² Brick/Block = 150-200 ft ² Concrete = 150-200 ft ² Split Rib Block = 80-100 ft ² |
| Application Temperature | Ambient & surface temperature must be 32°F or above and will not fall below that for 48 hours |
| Mixing | Stir well. Not to be thinned. * Transeal Clear Matte must be mixed before use and continuously during use |
| Dry Time | 12-24 hours at 70°F, 50% RH |
| Recoat Time | 6 hours at 70°F, 50% RH |



Phone: 800-442-5535
Fax: 978-453-2416
www.umaco.com