

# TRANSEAL WB



**TRANSEAL WB** is a clear, low odor, water based, acrylic sealer designed to be applied over properly prepared concrete pavers, brick, block, concrete, stucco, natural stone, flagstone, granite, limestone and bluestone. Forms a durable, flexible film providing long lasting protection.

- Low odor & VOC compliant
- Leaves a Gloss finish which highlights the beauty & color of natural stone, flagstone, granite, bluestone and pavers
- Protects against repeated freeze thaw cycles
- Easily applied with brush, roller or spray
- Forms a durable, flexible film
- Protects against repeated freeze thaw cycles.
- Reduces efflorescence
- Quick drying

Masonry Sealer	May be applied by brush, roller or low pressure pump sprayer
Packaging	1G can (4/case,108/pallet) 5G pail (36/pallet), 55G drum
Coverage per gallon	Slate/Flagstone = 250-350 ft <sup>2</sup> Brick/Block = 150-250 ft <sup>2</sup> Concrete = 150-250 ft <sup>2</sup> Split Rib Block = 75-150 ft <sup>2</sup>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing	Stir well. Not to be thinned.
Dry Time	12-24 hours at 70°F, 50% RH
Recoat Time	6 hours at 70°F, 50% RH



Phone: 800-442-5535  
 Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)