

# U-TROWEL



**U-TROWEL** is a cement based, waterproof stucco designed to be applied by trowel over properly prepared concrete, masonry, cement board and exterior grade plywood sheathing (when covered with water resistant building paper and galvanized wire lath embedded in U-Trowel Basecoat).

- One trowel coat required when applied directly over most masonry and concrete surfaces
- Eliminates costly rubbing and grinding of poured concrete
- Produces a durable finish
- May be applied in a wide variety of textures
- May be used for swimming pools, fountains & other emersion applications
- Exhibits superior adhesive bond, compressive, tensile and flexural strengths

Stucco	Apply by trowel from 1/8" up to 1/4"
Packaging	50 lb bag (49/pallet)
Coverage per 50 lb bag	1/8" = 50 ft <sup>2</sup> 1/4" = 25 ft <sup>2</sup>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing per 50 lb bag	<ul style="list-style-type: none"> <li>• 1 quart Addmix-35</li> <li>• 3 quarts of water</li> </ul>
Working Time	15-30 minutes at 70°F
Set Time	24 hours at 70°F
Colors	Gray and White



Phone: 800-442-5535  
 Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)