

# MP TILE MORTAR



**MP TILE MORTAR** is a cement based, polymer modified setting mortar for ceramic tile, vitreous & non-vitreous tile, quarry tile, marble and granite.

**MP TILE MORTAR** bonds to structurally sound concrete, plywood, gypsum board, ceramic tile and reinforced cement board.

- High performance
- Polymer modified
- High bond and flexural strength
- Sets ceramic tile, vitreous & non-vitreous tile, quarry tile, marble and granite
- Bonds to concrete, plywood, gypsum board, ceramic tile and reinforced cement board
- Walls, floors and ceilings
- Interior or exterior use
- Highly impact resistant
- Resists vibration and thermal shock

Mortar/ Adhesive	Apply using notched trowel
Packaging	50 lb bag (49/pallet)
Coverage per 50 lb bag	<ul style="list-style-type: none"> <li>• 70-80 ft<sup>2</sup> (1/4" x 1/4")</li> <li>• 50-60 ft<sup>2</sup> (1/4" x 3/8")</li> </ul>
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing per 50 lb bag	5 quarts of water
Working Time	30 minutes at 70°F
Set Time	24 hours at 70°F
Colors	Gray and White



Phone: 800-442-5535  
 Fax: 978-453-2416  
[www.umaco.com](http://www.umaco.com)