

SILOXANE 20



SILOXANE 20 is an exterior grade, solvent based, clear, deep penetrating water repellent designed to be applied over untreated concrete pavers, brick, block, concrete, stucco, flagstone, granite, natural stone, limestone and bluestone. Breathable, does not form a film or leave a sheen.

- Breathable, does not form a film or leave a sheen
- Dries clear on most substrates maintaining the natural appearance
- Easily applied by brush, roller or low pressure pump sprayer
- Protects against repeated freeze thaw cycles
- UV light resistant
- Reduces efflorescence
- VOC compliant
- One coat coverage for most applications
- Exterior use only

Water Repellent	May be applied by brush, roller or low pressure pump sprayer
Packaging	1G can (4/case,108/pallet) 5G pail (36/pallet), 55G drum
Coverage per gallon	Concrete = 120-220 ft ² Block/Brick = 80-150 ft ² Split Rib Block = 50-100 ft ²
Application Temperature	Ambient & surface temperature must be 32°F or above and will not fall below that for 48 hours
Mixing	Not to be thinned
Dry Time	12-24 hours at 70°F, 50% RH
Recoat Time	If second coat is required, must be applied wet-on-wet



Phone: 800-442-5535
Fax: 978-453-2416
www.umaco.com