

U-TROWEL BASECOAT



U-TROWEL BASECOAT is a blend of Portland cement, select aggregates & alkaline resistant fibers designed to be used as a basecoat for U-Trowel, Finish-Coat, manufactured stone and thin stone veneers.

- A basecoat for U-Trowel, Finish-Coat, manufactured stone & thin stone veneer
- May be applied over properly prepared concrete, masonry and exterior-grade plywood sheathing (when covered with building paper and galvanized 3.4 metal lath)
- Reinforces against plastic shrinkage crack formation
- Fibers are rustproof and corrosion resistant
- Increases impact resistance

Basecoat	Apply by trowel from 1/8" up to 1/4"
Packaging	50 lb bag (49/pallet)
Coverage per 50 lb bag	<u>Over Concrete/Masonry</u> 1/4" = 25 ft ² <u>Over Metal Lath</u> 1/4" = 15-20 ft ²
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Mixing per 50 lb bag	<ul style="list-style-type: none"> • 1 quart Addmix-35 • 3 quarts of water
Working Time	15-30 minutes at 70°F
Set Time	24 hours at 70°F
Color	Gray



Phone: 800-442-5535
 Fax: 978-453-2416
www.umaco.com